

A HIGHER FORM OF FUNCTION



BRETTFORD

LEGACY™ GRAND 4-LEG CHAIR

- ▶ The Grand Four-Leg Chair is a sturdy chair line that includes a chair, armchair and matching barstool. The side rails are extra thick to support the weight of people climbing up and leaning onto the chair next to them. The back slats are raised from the seat to allow for easy cleaning.



LHB035 Grand 4-Leg Chair with upholstery / LHB035S Grand 4-Leg Chair with arms / Standard Cherry

LEGACY™ GRAND 4-LEG CHAIR



Grand 4-Leg Barstool - wood seat

Grand 4-Leg Chair - wood seat



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852

WWW.BRETTFORD.COM

KEY FEATURES

All chairs constructed of 100% solid European beech hardwood.

Seats are available with upholstery or without.
All chairs are available stained to match any Legacy Library Environments product.

DIMENSIONS

CHAIR

OVERALL

19"d x 17-3/4"w x 35"h (48.3 x 45 x 88.9cm)

SEAT SIZE

16-1/2"d x 17-3/4"w (41.9 x 45cm)

SEAT HEIGHT

18"h (45.7cm)

BARSTOOL

OVERALL

19-1/2"d x 17-3/4"w x 47"h (49.5 x 45 x 119cm)

SEAT SIZE

16.5"d x 17-3/4"w (41.9 x 45cm)

SEAT HEIGHT

30"h (76cm)

ARMCHAIR

OVERALL

19"d x 21-1/2"w x 35"h (48.3 x 54.6 x 88.9cm)

SEAT SIZE

16.5"d x 17-3/4"w (41.9 x 45cm)

SEAT HEIGHT

18"h (45.7cm)

CONSTRUCTION

JOINTS

Mortise and tenon. Glued with high solids glue and reinforced with 18-gauge nails, corner blocks and low root wood screws.

9-STEP FINISHING PROCESS

1. The bare wood of the assembled chair is thoroughly sanded using 120 grit paper.
2. One coat of stain is sprayed onto the entire chair, including the underside of the seat.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.
4. The chair is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood, including the underside of the seat.
6. Once dry, the sealer is sanded using 320 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.