

3782 / 3783 3792 / 3793

12" [305] Rough-in, Low Consumption Closet Combination Vitreous China



• 3782 Galaxy® Elite II

Bowl: 3352 Galaxy® II regular rim vitreous china (1.6 gpf / 6.0 lpf), siphon jet action with bolt caps.

Tank: 3742 Galaxy® Elite 12" [305] roughing-in vitreous china tank and cover with flush valve, float valve with backflow preventer, and color coordinated trip lever.

• 3783 Galaxy® Elite II Plus

Bowl: 3352 Galaxy® II regular rim vitreous china (1.6 gpf / 6.0 lpf), siphon jet action with bolt caps.

Tank: 3743 Galaxy® Elite Plus 12" [305] roughingin insulated vitreous china tank and cover with flushvalve, float valve with backflow preventer, and color coordinated trip lever.

• 3792 Galaxy® Elite II

Bowl: 3372 Galaxy® II elongated rim vitreous china (1.6 gpf / 6.0 lpf), siphon jet action with bolt caps.

Tank: 3742 Galaxy® Elite 12" [305] roughing-in vitreous china tank and cover with flushvalve, float valve with backflow preventer, and color coordinated trip lever.

• 3793 Galaxy® Elite II Plus

Bowl: 3372 Galaxy® II elongated rim vitreous china (1.6 gpf / 6.0 lpf), siphon jet action with bolt caps.

Tank: 3743 Galaxy® Elite Plus 12" [305] roughingin insulated vitreous china tank and cover with flushvalve, float valve with backflow preventer, and color coordinated trip lever.

Supply:

Seat:

Color:



NOTES

- Fixture conforms to ANSI/ASME A112.19.2M standard.
- Also available with right hand trip lever tank model number 3746.

WATER ECONOMY FACTS

Average Gallons Per Flush	20 PSI	50 PSI	80 PSI
3782, 3783 Regular Rim (gpf)	1.50	1.58	1.59
3782, 3783 Regular Rim (lpf)	5.67	5.97	6.01
3792, 3793 Elongated Rim (gpf)	1.40	1.47	1.54
3792, 3793 Elongated Rim (lpf)	5.29	5.56	5.82
TRAPWAY2" [51]			
WATER SURFACE10" [254] x 8" [203]			
WATER SEAL2 5%" [67]			



3782 / 3783 3792 / 3793

12" [305] Rough-In Low Consumption Combination

