NSTITUTIONAL SHOWER MODULE A 6038.03GU



NOTES

- Anti-skid floor treatment meets performance requirements of ASTM F-462-78.
- The basic shower conforms to ANSI Z124.2.

• Nominal Dimensions: Inside: 54" x 36"

Outside: 60 3/4" x 38" Roughing-In: 61 1/4" x 38 1/2"

· Factory installed components are provided with additional back reinforcements to provide code complying structural integrity. In addition, these components are sealed from the backside.

OPTIONS

- · Pressure balanced, single lever mixing valve with stops. (180AA)
- · Thermostatically controlled single lever mixing valve with stops. (T162AA)
- Hand-held shower with swivel fitting, 69" flexible stainless steel hose, and in-line vacuum breaker. (H11)
- 24" slide guide. (For hand-held shower attachment.) (H12)
- Dome light. (ATP1)
- 2" plastic drain with chrome plated strainer. (PD2)
- 2" cast brass drain with chrome plated strainer. (H30)
- White shower curtain with hooks. (C4)
- Lucite® acrylic sheet containing Microban® antimicrobial product protection. Available in white and bone only. (MBP)

Lucite is a registered trademark of INEOS Acrylics, Inc. Microban is a registered trademark of Microban Products Company, Huntersville, NC.

One Piece Shower Module Cast Acrylic

FEATURES

A 6038.03 GU

The unit is molded with a shampoo/soap shelf centered on the back wall. Shower modules shall be pre-drilled for a valve and a handheld shower head when factory supplies components. All units have an anti-skid floor treatment.

Unit must be set in a mortar base, leveled and any clearances between the opening and the unit be filled with mortar. Shimming is necessary. It is recommended that a floor drain at or near the entrance to the shower be included.

The factory supplied components are to include one stainless steel full wrap around grab bar, two stainless steel vertical grab bars and a stainless steel curtain rod.

The unit is thermoformed from continuous cast acrylic sheet into a one piece seamless unit. The unit is reinforced with a composite matrix. The unit has a backside fire rating of "A" and a flame spread of 25.



One Piece Cast Acrylic Institutional Shower Module



