

255 Montpellier, St. Laurent (Montreal) QC, Canada H4N 2G3 Tel: (800) 638-5726 Fax (514) 744-2716 www.simplexceilings.com

Specifications

Clip-On Series

Panels: Provide Simplex Clip-on system manufactured from 0.032" (0,81mm), 0.040" (1.0 mm), thick aluminum, galvanized

steel, and stainless steel. Panel is downward demountable with a [butt joint, 1/8" (3mm) or 1/4" (6mm) reveal] and clip into a standard 15/16" T-bar grid. Panel dimensions will be as shown on drawings. Panels to be un-perforated or

perforated with a un-perforated border, using pattern defined by the architect.

Finish: Select from Simplex Ceiling standards for panels. Custom colors available upon request.

Suspension: Suspension shall be 15/16" (24mm) T-bar with standard mains and cross tees.

Perimeter: Provide Box Mould with Hold down Clips as required in finish to match panels.

Acoustical: For perforated panels, provide a 0.008" (0.2mm) thick Simplex "T" non-woven acoustical textile to be bonded to the

inside face of the panels. Can also be provided in 1-1/2" (38 mm) thick x 3/4 lb/cu.ft (12 kg/m³) density glass wool fiber completely sealed in an incombustible bag and installed with accordion pad spacers placed between the panel back and

acoustical pad.

Standard Sizes: 12" x 12" 12" x 24" 12" x 36" 12" x 48"

12" x 60" 24" x 24" 24" x 48"

Metric Sizes (mm): 305 x 305 305 x 610 305 x 914 305 x 1219

305 x 1524 610 x 610 610 x 1219

(Other custom sizes available upon request)

