



SIMPLEX®

CEILINGS

255 Montpellier, St. Laurent
(Montreal) QC, Canada H4N 2G3
Tel: (800) 638-5726 Fax (514) 744-2716
www.simplexceilings.com

Specifications

Quad Series

- Panels:** Provide Simplex Ceilings Quad panel system manufactured from {0.032" (0.81 mm), 0.040" (1.016 mm)} thick aluminum. Panel and Beam dimensions will be as shown on drawings. Panels are to be [un-perforated, perforated using pattern #___ with a {standard, ___ in. un-perforated border}].
- Finish:** Select from Simplex Ceilings' standards. Custom colors available upon request.
- Suspension:** Provide Simplex Ceilings Quad suspension type to form a module of _____ inch by _____ inch. Grid Beams shall be _____ inch wide by _____ inch, shown on drawings with appropriate perimeter treatment. All outside corners must be mitered. Provide all hanger couplers and corner brackets necessary to suspend ceiling. Exposed floating perimeter beam will have un-notched visible surfaces. Provide factory cut-outs for sprinklers, spot lights, etc...
- Perimeter:** Provide L-mould, Perimeter Beams or combination of Perimeter beam and "L" mould for wall to wall, floating or a combination application.
- Acoustical:** For perforated panels, provide 1 ½" (38mm) thick x ¾ lbs /cu ft (12 kg/cu m) density glass wool fiber completely sealed in a black incombustible (Class A) bag. Alternatively, provide Simplex "T" non-woven acoustical liner laminated to back of perforated panel.
- Accessibility:** System is upwards demountable, providing point accessibility.
- Standard Sizes:** 24" x 24" and 24" x 48"
- Metric Sizes (mm):** 610 x 610 and 610 x 1219
(Other custom sizes available upon request.)

