

255 Montpellier, St. Laurent (Montreal) QC, Canada H4N 2G3 Tel: (800) 638-5726 Fax (514) 744-2716 www.simplexceilings.com

Specifications

Cell 9-IG Series

Panels: Provide Simplex Ceilings Cell 9-IG system manufactured from 0.020" (0,51mm) thick aluminum. Blade

dimensions will be 3/8" (10 mm) width x cell heights shown below. Cell sizes are available in dimensions shown below. Blades are factory assembled into 24" x 24" (610 mm x 610 mm) panels or can be shipped knock-down to

reduce freight bulk & costs.

Panel Size: (Module) 24" x 24" (610 mm x 610 mm). Custom sizes available upon request.

Finish: Select from Simplex Ceiling standards for Open Cell Series. Custom colors available upon request

Suspension: Main hanger runners to be 72" (1829 mm) long supported on 36" (915 mm) centers and spaced on 48" (1219 mm)

centers. Cross runners 48" (1219 mm) long and 24" (610 mm) long are die punched and notched to support the 24"

x 24" (610 mm x 610 mm) modules.

Perimeter: Provide 1" x 2" x 96" (25 mm x 51 mm x 2439 mm) Wall Angle as required in finish to match modules (wall to


wall applications).

Provide 1-1/8", 1-916" or 2" (30 mm, 40 mm or 50 mm) x 48" (1219 mm) Perimeter Channel as required in finish

to match panels (floating ceiling applications).

CELL SIZES: CELL HEIGHT (NOMINAL DIMENSIONS)

50 mm x 50 mm	(2" x 2")	30 mm	(1-1/8'')
75 mm x 75 mm	(3" x 3")	40 mm	(1-9/16")
86 mm x 86 mm	(3.4" x 3.4")	50 mm	(2")
100 mm x 100 mm	(4" x 4")		
120 mm x 120 mm	(4.75" x 4.75")		
150 mm x 150 mm	(6" x 6")		
200 mm x 200 mm	(8" x 8")		
300 mm x 300 mm	(12" x 12")		



Typical Simplex Cell 9-IG 100 mm x 100 mm x 50 mm shown Perimeter Channel Cross Runner 24" (610 mm)

Cross Runner 48" (1219 mm) (Hanger Runner 72" (1829 mm) not shown)



255 Montpellier, St. Laurent (Montreal) QC, Canada H4N 2G3 Tel: (800) 638-5726 Fax (514) 744-2716 www.simplexceilings.com

Specifications

Open Cell 9-IG Series

Assembly Detail for Cell 9-IG Series

