



SIMPLEX®

CEILINGS

255 Montpelier, St. Laurent
(Montreal) QC, Canada H4N 2G3
Tel: (800) 638-5726 Fax (514) 744-2716
www.simplexceilings.com

Specifications

Linar Series

Panels: Provide Simplex Linar (L-75/100/100-L/150-L) systems manufactured from 0.022 in (0.56 mm) thick aluminum. Panel dimension will be as shown at table below). A separate filler strip 1" (25 mm) wide will snap into indentations in the panel sides, to ensure positive locking to panels. All dimensions nominal.

PANEL SIZES

	WIDTH	HEIGHT	Profile: Linar L-75	Profile: Linar L-100	Profile: Linar L-100L & L-150L
Linar L-75	2" (50 mm)	x 1-5/8" (42 mm)			
Linar L-100	3" (75 mm)	x 1-1/8" (30 mm)			
Linar L-100-L	3" (75 mm)	x 3/4" (20 mm)			
Linar L-150-L	5" (125 mm)	x 3/4" (20 mm)			

Finish: Select from Simplex Ceilings Inc. Metal Standard color finishes. Custom colors are available upon request.

Carriers: **Interior:** Linar "U" series carrier and twist type suspension clips to be 4' (1,219 mm) centers.
Exterior: Linar "U" series carrier attached to horizontal channels and down braced as required. Carriers to be installed on 3' (914 mm) centers unless otherwise noted.

Fillers: As shown in standard black PVC, perforated aluminum fillers optional. Fillers snap into formed V-groove in panels sides.

Perimeter: Provide L-mould or C-mould as required in finish to match panels

Accessories: Supply face plates for all down lights and ceiling speakers finish matching panels and twist suspension clips.

