



# **SIMPLEX<sup>®</sup>**

## **CEILINGS**

255 Montpelier, St. Laurent  
(Montreal) QC, Canada H4N 2G3  
Tel: (800) 638-5726 Fax (514) 744-2716  
www.simplexceilings.com

### Specifications

## Curved Generation 2000 Series

- Panels:** Provide Simplex Ceilings Curved Generation 2000 system manufactured from minimum 0.040" (1.016 mm) thick aluminum. Plank dimensions will be as shown on drawings. Planks to be [un-perforated, perforated using pattern #\_\_\_ with a {standard, \_\_\_ in. un-perforated border}].
- Finish:** Select from Simplex Ceilings' standards. Custom colors available upon request.
- Suspension:** Suspension shall be extruded aluminum Z-bar, to be attached to (1 ½") or (2") "black iron" channel with adjustable Locking Suspension Brackets
- Perimeter:** Provide curved L-mould or straight Box-mould with hold down clips as required in finish to match panels.
- Acoustical:** For perforated panels, provide 1 ½" (38mm) thick x ¾ lb./cu ft (12 kg/cu m) density glass wool fiber completely sealed in a black incombustible (Class A) bag. Alternatively, provide Simplex "T" non-woven acoustical liner laminated to back of perforated panel.
- Accessibility:** System is upwards demountable, providing point accessibility.
- Standard Sizes:** 24"x 24", 24" x 36", 24"x 48", 24"x 60", 24"x 72", 24"x 84", 24" x 96" and 24" x 120"
- Metric Sizes (mm):** 610 x 610, 610 x 914, 610 x 1219, 610 x 1524, 610 x 1828, 610 x 2133, 610 x 2438 and 610 x 3048  
(Other custom sizes available upon request.)

