

PHYSICAL CONSTRUCTION:

| | |
|----------------------|---|
| CONSTRUCTION: | Graphic Loop |
| FACE FIBER: | Type 6,6 Nylon |
| DYE METHOD: | Solution |
| GAUGE: | 1/10 |
| STITCHES PER INCH: | 13.66 |
| PILE THICKNESS: | .096 Inches |
| DENSITY: | Average Density = 4,125; Weight Density = 45,375 |
| PRIMARY BACKING: | 100% Synthetic |
| PRIMARY PRECOAT: | 100% Non-Aqueous Polymer, Providing 15 Year Warranty Against Stain Wick-Back |
| SECONDARY BACKING: | Mannington Modular Backing System with Non-Woven Fiberglass Stabilizing Layer |
| STANDARD SIZE: | 24" X 24" Modular Tiles |
| INSTALLATION METHOD: | Quarter-Turn or Brick Ashlar; Other Methods at Owner's Discretion |

ENVIRONMENTAL:

| | |
|--------------------------|---|
| RECYCLED CONTENT: | Contains Pre-Consumer Recycled Content* |
| MANUFACTURE LOCATION: | Calhoun, Georgia 30701 USA |
| CRI GREEN LABEL PLUS ID: | GLP7616 |

WARRANTIES:

| | |
|----------------------------|--|
| WARRANTY: | 15 Year Limited Warranty, Including Face Wear, Moisture Barrier, Wick-Back, Delamination, Tuft Bind, Unraveling, and Static Protection |
| BLEACH RESISTANT WARRANTY: | ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills |
| STAIN RESISTANT WARRANTY: | XGUARD with 15 Year Limited Warranty Against Staining |

PRODUCT TESTING:

| | |
|---------------------------------------|------------------------------|
| CRI TM101 APPEARANCE RATING: | Heavy Traffic |
| RADIANT PANEL (ASTM E-648): | Class I (Direct Glue) |
| SMOKE CHAMBER (ASTM-E-662): | Less than 450 (Flaming Mode) |
| METHENAMINE PILL TEST (ASTM D-2859): | Passes |
| DIMENSIONAL STABILITY AACHEN TEST: | Passes |
| ELECTROSTATIC PROPENSITY (AATCC 134): | Less than 3.0 KV |

RECOMMENDED ADHESIVE:

| | |
|--------------------------|--|
| RELEASEABLE ADHESIVE: | Mannington Infinity Pressure Sensitive Adhesive |
| CRI GREEN LABEL PLUS ID: | GLP70522 |
| VOC LIMITS: | Meets SCAQMD Rule #1168 |
| BOND WARRANTY: | Lifetime Limited Warranty When Used With Mannington Carpet |

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.