

VG 231 214CA

Stainless steel control panel Natural gas Width 12" (29 cm)

Installation accessories

VV 200 014

Connecting strip for combination with other Vario cooktops

Optional accessories

VD 201 014

Brushed stainless steel appliance cover

WP 400 001

Wok pan made of multiple-layered material with round bottom and handle, ø 14 ¾16", height 3 15/16".

Due to its diameter, do not combine with the VL 041/040 and air baffle LS 041 000.

200 series Vario gas wok cooktop

Equipped for natural gas. Jets supplied for conversion to LP gas.

- Special appliance for restaurant-grade capabilities in the home kitchen.
- Generous control panel for comfortable and secure operation.
- Wok burner with 17,000 BTU output. For the typical Asian quick braising and for large pots and pans.
- Electric ignition of burner.
 Simply press the knob, turn it and hold it there until a stable flame burns.

Cooking zones

1 three-ring wok burner. (250–5,000 W) 850 - 17,000 BTU, suitable for woks and pans up to ø 12 $^5\!/\!\mathrm{s}^{\shortparallel}$.

Features

Brushed stainless steel cooktop. Three flame rings.
Electric ignition.
Cast-iron pan support.
Three-ring burner of solid heat-resistant burner brass.

Safety

All-gas valve with fine control thermoelectric safety pilot.

Planning notes

Maximum drawer depth 16 $\%_{16}$ ". Appliance clicks into place when inserted in the countertop from above.


A minimum clearance of 5 %" from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation must be installed.


The gas cooktop is equipped with a connecting cable and a shock-proof plug (55" long).

Rating

Total rating: 17,000 BTU Total Amps: 1 120V / 60Hz

Gas connection





Numbers indicated inside parenthesis () = mm