



AI 280 720

Stainless steel

Width 48" (120 cm)

Air extraction/recirculation

Installation accessories for exhaust air mode

AD 280 016

Stainless steel duct cover,
for ceiling heights 7'5" - 8'
(2.27 m - 2.44 m)

AD 280 026

Stainless steel duct cover,
for ceiling heights 8' - 9'
(2.44 m - 2.76 m)

AD 280 036

Stainless steel duct cover,
for ceiling heights 9' - 9'9"
(2.76 m - 2.98 m)

Installation accessories for recirculation air mode (order activated charcoal filter separately):

AD 280 126

Stainless steel duct cover,
for ceiling heights 8' - 9'
(2.44 m - 2.76 m)

AD 280 136

Stainless steel duct cover
for ceiling heights 9' - 9'9"
(2.76 m - 2.98 m)

KF 001 010

Activated charcoal air filter

Island hood

AI 280

- Optimized Coanda effect,
for high extraction efficiency
at both sides
- Standard operation at lower
output levels
- Reduced energy consumption
and less noise
- Air extraction or recirculation
system
- Operation from both sides

Output

Unobstructed air flow:

Max. air output 400 CFM.

Sound pressure level:

Air extraction 49 dB.

Features

Controls on both sides.

3 electronically controlled
output levels.

Intensive mode with permanent
Coanda effect in the front
and back.

Interval ventilation.

Delayed shut-off function.

Grease filter saturation indicator.

Stainless-steel filter, dishwasher-
safe.

Fully illuminated surface with
compact fluorescent tube

2 x 36 Watts.

Planning notes

A large drop in output and sig-
nificantly increased noise can be
expected in the air recirculation
mode in the case of ventilation
hoods with a very high air output.
Clearance above gas and electric
appliances min. 30".
Fit the plug concealed behind ven-
tilation duct.

Weight 99 lbs.

Recommendation for stainless
steel parts that have to be welded
and polished to match hood:
brushed grain 280.

Surfaces: Stainless steel 1.4016,
ground and brushed IIC.

The dimensions of the air duct
covers refer to a distance of 63"
from the floor to the bottom edge of
the hood. Convert for other
installation heights: countertop
height + minimum clearance +
hood with duct cover.

Rating

Total rating: 335 W.

Total Amps: 3.3

120 V / 60 Hz

Connecting cable 52" with plug.

Air extraction:

AD 280 016 = 26 ³/₈" - 33 ¹/₁₆" (670-840 mm)


AD 280 026 = 33 ¹/₁₆" - 45 ¹¹/₁₆" (840-1160 mm)

AD 280 036 = 45 ¹¹/₁₆" - 54 ⁵/₁₆" (1160-1380 mm)

Recirculation air:

AD 280 126 = 33 ¹/₁₆" - 45 ⁵/₁₆" (840-1160 mm)

AD 280 136 = 45 ¹¹/₁₆" - 54 ⁵/₁₆" (1160-1380 mm)



Numbers indicated
inside parenthesis () = mm