

Face Construction	IMPERIAL	METRIC
Construction	Tufted Textured Loop	
Tufted Pile Weight	16.0 oz/sq yd	542 g/sq m
Gauge	1/10 inch	39.4 rows/10 cm
Stitches per Inch	11.6 stitches / inch	45.7 stitches/10 cm
Finished Pile Height	0.177 inch	4.5 mm
	0.079 inch	2.0 mm
Total Finished Weight	54.2 oz/sq yd	1837 g/sq m
Density	4347	
Kilotex	8.3	
Fiber System	Dynex SD® nylon/Dynex® nylon	
Dye Method	76.85% Solution / 23.15% Space Dyed	
Pattern Repeat	2.40" W x 5.17" L	61 mm W x 131 mm L
Soil Protection	ENSURE	
Primary Backing	Woven Polypropylene	
Backing Construction	Super-Lok® enriched latex backing	
Width	12 feet	366 cm
Custom Options	500 sq yd + 5% overmake	

**Color Line**

01881 Surface Rust	01885 Conservatory	01889 Milestone
01882 Fall Term	01886 Pocket Watch	01890 Watercolor
01883 Collage	01887 Paperie	01891 Blazer
01884 Glasshouse	01888 Transparent	01892 Bleu

**Product Testing/Information**

IAQ Results	CRI Green Label Plus Registration Number GLP9878. (Low VOC emitter.)	
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70
	Flooring Radiant Panel	ASTM E-648 Class 1 (Direct Gluedown)
	Smoke Density	ASTM E-662 Less than 450
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

**Warranties**

10 Year Limited Abrasive Wear
Lifetime Limited Anti-Static (Less than 3.5 kv)
10 Year Limited No Delamination or Edge Ravel

**Product Notes**

All specifications are subject to normal manufacturing tolerances.  
 Dyelots may vary from samples.  
 The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.  
 Tandus Flooring reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

**Installation and Maintenance**

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.  
 To achieve best results, more time should be allowed to install patterned carpet. This style has a definite pattern and must be installed according to pattern match procedures as outlined in Tandus Flooring installation specifications, available from your Tandus Flooring Representative.  
 Manufacturing tolerances on Tandus Flooring tufted carpets are:  
 Bow - 3/4" per 12' width  
 Skew - 1" per 12' width  
 Edge Straightness - +/- 1/2" variation  
 Pattern Elongation - 1 1/4" per 12' length  
 For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.  
 Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.  
 Recommendations are available from your Tandus Flooring Representative.

**Launch Date**

June 2011