

Face Construction	IMPERIAL	METRIC
Construction	Tufted Patterned Loop	
Tufted Pile Weight	20 oz/sq yd	678 g/sq m
Gauge	1/10 inch	39.4 rows/10 cm
Stitches per Inch	13.0 stitches / inch	51.2 stitches/10 cm
Finished Pile Height	0.197 inch	5.0 mm
	0.117 inch	3.0 mm
Total Finished Weight	58.2 oz/sq yd	1973 g/sq m
Kilotex	12.1	
Fiber System	Dynex SD® nylon	
Dye Method	Solution Dyed	
Pattern Repeat	24.0" W x 40.77" L	609.60 mm W x 1035.56 mm L
Soil Protection	ENSURE	
Backing Construction	Super-Lok® enriched latex backing	
Width	12 feet	366 cm

Color Line

01672 Transit	01674 Café	01671 Cinema
01679 City Market	01683 Eco Resort	01686 Radar
01680 Sand Rail	01684 Water Taxi	01687 Cosmopolitan
01670 Trench Coat	01676 Catamaran	01673 Signal
01681 Land View	01685 Jet Stream	
01682 Spa	01678 Metro	

Product Testing/Information

IAQ Results	CCI/CRI Green Label Plus Registration Number GLP9878. (Low VOC emitter.)	
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70
	Flooring Radiant Panel	ASTM E-648 Class I (Direct Gluedown)
	Smoke Density	ASTM E-662 Less than 450
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

Warranties

5 Year Limited Colourfastness (Atmospheric Fumes)
10 Year Limited Colourfastness (Light)
10 Year Limited Abrasive Wear
Lifetime Limited Anti-Static (Less than 3.5 kV)
10 Year Limited No Delamination or Edge Ravel

Product Notes

All specifications are subject to normal manufacturing tolerances.

Dyelot may vary from samples.

The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

Tandus Flooring reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.

To achieve best results, more time should be allowed to install patterned carpet. This styles has a definite pattern and must be installed according to pattern match procedures as outlined in Tandus Flooring installation specifications, available from your Tandus Flooring Representative.

Manufacturing tolerances on Tandus Flooring tufted carpets are:

- Bow - 3/4" per 12' width
- Skew - 1" per 12' width
- Edge Straightness - +/- 1/2" variation
- Pattern Elongation - 1 1/4" per 12' length

For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.

Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.

Recommendations are available from your Tandus Flooring Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at www.tandus.com/limitedwarranty and www.tandus.com/maintenance or by dialing 800-248-2878.