

| Face Construction | IMPERIAL | METRIC |
|-----------------------|-----------------------------------|----------------------------|
| Construction | Tufted Patterned Loop | |
| Tufted Pile Weight | 20 oz/sq yd | 678 g/sq m |
| Gauge | 1/10 inch | 39.4 rows/10 cm |
| Stitches per Inch | 13.0 stitches / inch | 51.2 stitches/10 cm |
| Finished Pile Height | 0.197 inch | 5.0 mm |
| | 0.117 inch | 3.0 mm |
| Total Finished Weight | 58.2 oz/sq yd | 1973 g/sq m |
| Density | 4571 | |
| Fiber System | Dynex SD® nylon | |
| Dye Method | Solution Dyed | |
| Pattern Repeat | 24.0" W x 66.15" L | 609.60 mm W x 1680.21 mm L |
| Soil Protection | ENSURE | |
| Backing Construction | Super-Lok® enriched latex backing | |
| Width | 12 feet | 366 cm |

Color Line

| | | |
|-------------------|------------------|--------------------|
| 01672 Transit | 01674 Café | 01671 Cinema |
| 01679 City Market | 01683 Eco Resort | 01686 Radar |
| 01680 Sand Rail | 01684 Water Taxi | 01687 Cosmopolitan |
| 01670 Trench Coat | 01676 Catamaran | 01673 Signal |
| 01681 Land View | 01685 Jet Stream | |
| 01682 Spa | 01678 Metro | |

Product Testing/Information

| | | |
|----------------------|--|--------------------------------------|
| IAQ Results | CCI/CRI Green Label Plus Registration Number GLP9878. (Low VOC emitter.) | |
| Surface Flammability | Methenamine Pill | Meets CAN/CGSB-4.129-93/DOC FF 1-70 |
| | Flooring Radiant Panel | ASTM E-648 Class I (Direct Gluedown) |
| | Smoke Density | ASTM E-662 Less than 450 |
| | Steiner Tunnel | ULC S102.2 Less than 300FS, 500SD |

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

Warranties

| |
|---|
| 5 Year Limited Colourfastness (Atmospheric Fumes) |
| 10 Year Limited Colourfastness (Light) |
| 10 Year Limited Abrasive Wear |
| Lifetime Limited Anti-Static (Less than 3.5 kV) |
| 10 Year Limited No Delamination or Edge Ravel |

Product Notes

All specifications are subject to normal manufacturing tolerances.

Dyelot may vary from samples.

The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

Tandus Flooring reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.

To achieve best results, more time should be allowed to install patterned carpet. This styles has a definite pattern and must be installed according to pattern match procedures as outlined in Tandus Flooring installation specifications, available from your Tandus Flooring Representative.

Manufacturing tolerances on Tandus Flooring tufted carpets are:

- Bow - 3/4" per 12' width
- Skew - 1" per 12' width
- Edge Straightness - +/- 1/2" variation
- Pattern Elongation - 1 1/4" per 12' length

For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.

Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.

Recommendations are available from your Tandus Flooring Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at www.tandus.com/limitedwarranty and www.tandus.com/maintenance or by dialing 800-248-2878.