

Face Construction	IMPERIAL	METRIC
Construction	Tufted Patterned Loop	
Tufted Pile Weight	22 oz/sq yd	746 g/sq m
Gauge	1/10 inch	39.4 rows/10 cm
Stitches per Inch	10.5 stitches / inch	41.3 stitches/10 cm
Finished Pile Height	0.157 inch	4.0 mm
	0.079 inch	2.0 mm
Total Finished Weight	60.2 oz/sq yd	2041 g/sq m
Kilotex	13.5	
Fiber System	Antron Lumena® nylon	
Dye Method	Solution Dyed	
Pattern Repeat	7.20" W x 2.29" L	182.9 mm W x 58.2 mm L
Soil Protection	ENSURE	
Primary Backing	Woven Polypropylene	
Backing Construction	Super-Lok® enriched latex backing	
Width	12 feet	366 cm

Color Line

02481 Cemented Metal	02493 Forged Iron	02515 Green Architecture
02482 Wood Pulp	02509 Organic Matter	
02483 Reclaimed Lumber	02510 Electroplated	
02484 Sandblasted	02512 Recycled Aluminum	
02489 Land Management	02513 Crushed Glass	
02490 Frozen Earth	02514 Solar Engine	

Product Testing/Information

IAQ Results	CRI Green Label Plus Registration Number GLP4478. (Low VOC emitter.)	
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70
	Flooring Radiant Panel	ASTM E-648 Class 1 (Direct Gluedown)
	Smoke Density	ASTM E-662 Less than 450
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

Warranties

5 Year Limited Colourfastness (Atmospheric Fumes)
10 Year Limited Colourfastness (Light)
10 Year Limited Abrasive Wear
Lifetime Limited Anti-Static (Less than 3.5 kv)
10 Year Limited No Delamination or Edge Ravel

Product Notes

All specifications are subject to normal manufacturing tolerances.
 Dyelots may vary from samples.
 The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.
 Tandus Flooring reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.
 Antron Lumena® nylon has been certified by Scientific Certification Systems as an Environmentally Preferable Product.

Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.
 To achieve best results, more time should be allowed to install patterned carpet. This style has a definite pattern and must be installed according to pattern match procedures as outlined in Tandus Flooring installation specifications, available from your Tandus Flooring Representative.
 Manufacturing tolerances on Tandus Flooring tufted carpets are:
 Bow - 3/4" per 12' width
 Skew - 1" per 12' width
 Edge Straightness - +/- 1/2" variation
 Pattern Elongation - 1 1/4" per 12' length
 For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.
 Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.
 Recommendations are available from your Tandus Flooring Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at www.tandus.com/limitedwarranty and www.tandus.com/maintenance or by dialing 800-248-2878.