

Face Construction	IMPERIAL	METRIC
Construction	Tufted Patterned Loop	
Tufted Pile Weight	21.0 oz/sq yd	712 g/sq m
Gauge	1/10 inch	39.4 rows/10 cm
Stitches per Inch	11.6 stitches / inch	45.7 stitches/10 cm
Finished Pile Height	0.177 inch	4.5 mm
	0.079 inch	2.0 mm
Total Finished Weight	59.2 oz/sq yd	2007 g/sq m
Kilotex	11.8	
Fiber System	Dynex SD® nylon/Dynex® nylon	
Dye Method	Solution/Yarn Dyed	
Pattern Repeat	7.20" W x 3.45" L	182.9 mm W x 87.6 mm L
Soil Protection	ENSURE	
Primary Backing	Woven Polypropylene	
Backing Construction	Super-Lok® enriched latex backing	
Width	12 feet	366 cm

### Color Line

02561 Sun Halo	02566 Blue Hue
02562 Visible Light	02567 Redshift
02563 Optical Filter	02568 Mica Powder
02564 Earth Pigment	02569 Black Shade
02565 Beta Beam	

### Product Testing/Information

IAQ Results	CRI Green Label Plus Registration Number GLP4478. (Low VOC emitter.)	
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70
	Flooring Radiant Panel	ASTM E-648 Class 1 (Direct Gluedown)
	Smoke Density	ASTM E-662 Less than 450
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

### Warranties

10 Year Limited Abrasive Wear
Lifetime Limited Anti-Static (Less than 3.5 kv)
10 Year Limited No Delamination or Edge Ravel

### Product Notes

All specifications are subject to normal manufacturing tolerances.
Dyelots may vary from samples.
The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.
Tandus Flooring reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

### Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.
To achieve best results, more time should be allowed to install patterned carpet. This style has a definite pattern and must be installed according to pattern match procedures as outlined in Tandus Flooring installation specifications, available from your Tandus Flooring Representative.
Manufacturing tolerances on Tandus Flooring tufted carpets are:
Bow - 3/4" per 12' width
Skew - 1" per 12' width
Edge Straightness - +/- 1/2" variation
Pattern Elongation - 1 1/4" per 12' length
For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.
Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.
Recommendations are available from your Tandus Flooring Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at [www.tandus.com/limitedwarranty](http://www.tandus.com/limitedwarranty) and [www.tandus.com/maintenance](http://www.tandus.com/maintenance) or by dialing 800-248-2878.