

L & S Illumination design



d5030 Stadio (14" diam.) and
d5029 Mini-Stadio (9½" diam.) pendants



d5030-1H100-120-CBL

d5030



Item #	Lamping	Voltage	Finish	Options	Sp. Orders

Work space for submittals

How to specify

Example from illustration at left

d5030	-1H100	-120	-AL		
-------	--------	------	-----	--	--

Item Number

d5030

STADIO pendant / L & S Illumination design

Construction

Spun aluminum or solid copper (new) shade. Polished chrome trim, clamps and loop. White opal acrylic diffuser. 5" diam. black canopy. Adjustable height, aircraft cables support fixture. Black, 3 conductor cord. 60" overall height. For standard ceiling junction box mounting. UL listed, cUL certified for dry, damp and wet locations.

Lamping/Wattage

Fixtures supplied less lamps.
Lamps may be ordered from d'ac.

**Ballast located in 6" diam. x 2" deep canopy. Canopy and rigid stem (only) finished in Polished Chrome.

*Remote "F-can" magnetic metal halide ballasts not to exceed 15 feet from lamp.

1N150

1H100

1FS23

1F13

1F18

1F26

1F32

1F42

1F57**

1F70**

1M70*

1M100*

1M150*

Incandescent, one 150 W, medium base, A type

Halogen, one 100 W, medium base, double encased, T type

Fluorescent, one 23W, medium base, triple tube compact

Fluorescent, one 13 W quad, 4 pin, electronic HPF ballast

Fluorescent, one 18 W quad, 4 pin, electronic HPF ballast

Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast

Fluorescent, one 32 W triple tube, 4 pin, electronic HPF ballast

Fluorescent, one 42 W triple tube, 4 pin, electronic HPF ballast

Fluorescent, one 57 W triple tube, 4 pin, electronic HPF ballast

Fluorescent, one 70 W triple tube, 4 pin, electronic HPF ballast

Metal halide, one 70 W, medium base, ED-17 type

Metal halide, one 100 W, medium base, ED-17 type

Metal halide, one 150 W, medium base, ED-17 type

Voltage

120

120V

277

277V

Finishes

See Page d9000
and d9000A
for color renderings

AL Brushed Aluminum

WH White Gloss

MG Metallic Grey

MB Matte Black

BZ Metallic Bronze

GM Metallic Green

RD Metallic Red

YL Bright Yellow

PA Polished Aluminum

G1 Light Grey

AN Metallic Anthracite

BC Black Crinkle

T1 Light Tan

SF Seafoam

RB Bright Red

SCF Special Finish—must supply paint chip

CPL Polished Copper (*lacquered*) CBL Brushed Copper (*lacquered*)

CPU Polished Copper (*unlacquered – will naturally tarnish over time*)

CBU Brushed Copper (*unlacquered – will naturally tarnish over time*)

Baked Enamels:

G2 Medium Grey

BG Black Gloss

CU Metallic Copper

T2 Medium Tan

BL Metallic Blue

MP Magenta Pink

New: Solid copper shade:
(also available on smaller
d5029 fixture)

Options

WET UL listed for wet and damp locations **STEM** Rigid, 1/2" diam. stem (aircraft cable and cord replaced by 1/2" diam. rigid stem and modified canopy)

COIL Coiled electrical cord. (Not an option for metal halide.)

TR Fixture can be modified for use with track systems.
(adapter & track supplied by others)

INCP Inner shade in raw copper vs. painted white (standard on fixture)
for copper finishes.

Special Orders

For modifications to dimensions, electrical requirements and other special orders,
please contact your d'ac representative.



420 RAILROAD WAY • PO BOX 262 • MAMARONECK, NY 10543 914.698.5959 • FAX 914.698.6061 daclighting.com

A Subsidiary of Nessen Lighting

A JJI Lighting Group Inc. Company