

Dijkstra Lampen design



d5182-1F32-120-AL



| Item # | Lamping | Voltage | Shade Color | Optional Finish | Sp. Orders |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| <input type="text"/> |

Work space for submittals

How to specify

Example from illustration at left

| | | | | | |
|--------------|--------------|-------------|------------|----------------------|----------------------|
| d5182 | -1F32 | -120 | -AL | <input type="text"/> | <input type="text"/> |
|--------------|--------------|-------------|------------|----------------------|----------------------|

| | | |
|--------------------|--------------|-----------------------------|
| Item Number | d5180 | 4 3/4" diam. VESTA pendant |
| | d5181 | 9 1/4" diam. VESTA pendant |
| | d5182 | 13 3/4" diam. VESTA pendant |
| | | Dijkstra Lampen design |

Construction Spun aluminum shade. White internal reflector for d5181 and d5182. Black, three conductor hanging cord. 60" overall height. Fluorescent versions enclose ballast in canopy. For standard wall junction box mounting. UL listed, cUL certified for dry locations.

| | | | |
|--------------------------|---------------|---|---|
| Lamping / Wattage | For d5180 | 1N60 | Incandescent, one 60 W, medium base, A type |
| | | 1H50 | Halogen, one 50 W, medium base, double encased, T type |
| | | 1F13 | Fluorescent, one 13 W, quad tube, 4 pin, electronic HPF ballast |
| For d5181 and d5182 | 1N100 | Incandescent, one 100 W, medium base, A type | |
| | 1F18 | Fluorescent, one 18 W, quad tube, 4 pin, electronic HPF ballast | |
| | 1F26 | Fluorescent, one 26 W, triple tube, 4 pin, electronic HPF ballast | |
| | 1F32 | Fluorescent, one 32 W, triple tube, 4 pin, electronic HPF ballast | |
| For d5182 only | 1F42 | Fluorescent, one 42 W, triple tube, 4 pin, electronic HPF ballast | |
| | 1M70* | Metal Halide, one 70 W, magnetic ballast, T6 type | |
| | 1M100* | Metal Halide, one 100 W, magnetic ballast, T6 type | |

**Ballast located in shade. Fixture enclosed with acrylic bottom diffuser. All fixtures are supplied less lamps. Lamps may be ordered from d'ac.*

| | | | | |
|----------------|------------|------|------------|------|
| Voltage | 120 | 120V | 277 | 277V |
|----------------|------------|------|------------|------|

Finish **AL** Brushed Aluminum

| | | | |
|--------------------------|---------------------------|--|---------------------------|
| Optional Finishes | WH White Gloss | G1 Light Grey | G2 Medium Grey |
| | MG Metallic Grey | AN Metallic Anthracite | BG Black Gloss |
| | MB Matte Black | BC Black Crinkle | CU Metallic Copper |
| | BZ Metallic Bronze | T1 Light Tan | T2 Medium Tan |
| | GM Metallic Green | SF Seafoam | BL Metallic Blue |
| | RD Metallic Red | RB Bright Red | MP Magenta Pink |
| | YL Bright Yellow | SCF Special Finish—must supply paint chip | |

Special Orders For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.