

Hoffmeister-Leuchten design



d5190-1F42-120

d5190



Item #	Lamping	Voltage	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

How to specify

Example from illustration at left

d5190	-1F42	-120	<input type="text"/>
-------	-------	------	----------------------

Item Number Construction

d5190

PRISMALO pendant / Hoffmeister-Leuchten

12" diam. clear acrylic, prismatic shade. Cast aluminum 5 1/4" diam. housing. Adjustable height, aircraft cables support fixture. 60" overall height. Black three conductor hanging cord. Ballast located in metallic grey housing. Clear, flat, bottom lens. For standard wall junction box mounting. UL listed, cUL certified for dry locations.

Lamping / Wattage

1N100

Incandescent, one 100 W, medium base, A type

1F13

Fluorescent, one 13 W, quad tube, 4 pin, electronic HPF ballast

1F18

Fluorescent, one 18 W, quad tube, 4 pin, electronic HPF ballast

1F26

Fluorescent, one 26 W, triple tube, 4 pin, electronic HPF ballast

1F32

Fluorescent, one 32 W, triple tube, 4 pin, electronic HPF ballast

1F42

Fluorescent, one 42 W, triple tube, 4 pin, electronic HPF ballast

1M70

Metal halide, one 70 W, medium base, ED-17 type, magnetic ballast

All fixtures are supplied less lamps. Lamps may be ordered from d'ac.

Voltage

120

120V

277

277V

Special Orders

For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.

