Adapt Modular

7559 Nesting

7569 Spirituality

7655 Incentive-ize

7676 Authenticity

7681 Next Gen

7729 Younique

7821 Invent

7828 Flex

7858 Define

7956 Life Shopping

7978 Connecting

7989 Personalize

PRODUCT SPECIFICATIONS

Style Name ..... Adapt Modular
Style Number BT185
Collection Name 24/7
Product Type ..... Modular
Installation Method ..... Monolithic, Quarter Turn
Construction ..... Tufted
Surface Appearance ..... Textured Patterned Loop
Nylon Type ..... Colorstrand® SD Nylon
Gauge ..... 1/10 (39.37 rows per 10 cm)
Pile Weight ..... 24.0 oz. per sq. yd. (814 g/m2)
Pile Thickness ..... 191" (4.85 mm)
Stitches Per Inch ..... 10.0 (39.37 per 10 cm)
Dye Method ..... Solution Dyed
Protective Treatment ..... Sentry Plus

Density 4,524
Weight Density 108,576
Backing Material ..... EcoFlex ICT
Pattern Repeat ..... Not Applicable
Size ..... 24" x 24" (.6096 m x .6096 m)
Flammability ..... ASTM E 648 Class 1 (Glue Down)
Smoke Density ..... ASTM E 662 Less Than 450
Static Propensity ..... AATCC-134 Under 3.5 KV
IAQ Green Label Plus 1098
CRI Appearance Retention Rating ..... Severe Traffic
Warranties: Lifetime Limited Modular Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static