Caliber Modular

Caliber Modular

7238 Pumice

7358 Breccia

7559 Opal

7568 Marble

7656 Gabbro

7688 Ore

7728 Chert

7858 Feldspar

7879 Basalt

7927 Shale

7948 Granite

PRODUCT SPECIFICATIONS

STYLE NUMBER BT282
STYLE NAME .....Caliber Modular
COLLECTION .....Bending Earth
PRODUCT TYPE .....Modular
INSTALLATION METHOD .....Monolithic , Quarter Turn , Vertical Ashlar,
..... Brick Ashlar , Multi-Directional
CONSTRUCTION .....Tufted
RECYCLED CONTENT .....Contains a minimum 35% pre-consumer
.....recycled content by total weight
SURFACE APPEARANCE .....Level Patterned Loop
NYLON TYPE .....Colorstrand® SD Nylon
GAUGE .....1/12 (47.00 rows per 10cm)
PILE WEIGHT .....17.0 oz. per sq. yd. (576 g/m2)
PILE THICKNESS .....123" (3.12 mm)
STITCHES PER INCH .....9.2 (36.22 per 10 cm)
DYE METHOD .....Solution Dyed
PROTECTIVE TREATMENT .....Sentry Plus
DENSITY 4,976
WEIGHT DENSITY 84,592
BACKING MATERIAL .....EcoFlex ICT
PATTERN REPEAT .....Not Applicable
SIZE .....24" x 24" (.6096 m x .6096 m)
FLAMMABILITY .....ASTM E 648 Class 1 (Glue Down)
SMOKE DENSITY .....ASTM E 662 Less than 450
STATIC PROPENSITY .....AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS 1098
CRI APPEARANCE RETENTION RATING.....Heavy Traffic
WARRANTIES: Lifetime Limited Modular Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static