



MODULAR SPECIFICATIONS




Style Number.....	GT086
Style Name	Connexion Modular
Construction	tufted
Surface Texture.....	textured patterned cut and loop
Gauge	1/12 (47.00 rows per 10 cm)
Density.....	9,853
Weight Density	256,178
Stitches Per Inch.....	14.2 (55.91 per 10 cm)
Protective Treatment...	DuraTech
Finished Pile Thickness	.095" (2.41 mm)
Dye Method	solution dyed/yard dyed
Backing Material.....	EcoFlex ICT
Fiber Type	Duracolor® Premium Nylon with Antron® Legacy
Fiber Technology	Duracolor® by LEES Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight.....	26 oz/yd2 (881.66 gm/m2)
Size/Width	24" x 24" (60.9 cm x 60.9 cm)
Installation Method.....	monolithic
IAQ Green Label Plus..	1098
CRI Rating.....	Severe Traffic
Pattern Repeat	Not Applicable
Warranties	Lifetime Limited Modular Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static



104
BIRCH




108
SEASPRAY



124
BAMBOO SPROUT



201
BEACH GLASS



204
RIVERBEND



208
HEMATITE



301
NATURE'S ESSENCE



308
BRONZE SCULPTURE



348
NAUTICA



403
BONFIRE



408
STORM



508
NORDIC SHADOW