First One Up Modular

First One Up Modular

7343 Endless

7555 Celestial

7656 Ephemeral

7728 Physical

7737 Civil

7767 Eternity

7828 Worldly

7868 Transitory

7915 Global

7969 Logic

7979 Alluvial

7989 Dimension

PRODUCT SPECIFICATIONS

Style Name ..... First One Up Modular
Style Number BT286
Product Type ..... Modular
Installation Method ..... Monolithic, Vertical Ashlar,
..... Brick Ashlar, Quarter Turn, or
..... Multi-Directional
Construction ..... Tufted
Surface Appearance ..... Textured Patterned Loop
Nylon Type ..... Colorstrand® SD Nylon
Gauge ..... 1/12 (47.00 rows per 10 cm)
Pile Weight ..... 22.0 oz. per sq. yd. (746 g/m2)
Pile Thickness ..... 109" (2.77 mm)
Stitches Per Inch ..... 9.0 (35.43 per 10 cm)
Dye Method ..... Solution Dyed
Protective Treatment ..... Sentry Plus

Density 7,266
Weight Density 159,852
Backing Material ..... EcoFlex ICT
Pattern Repeat ..... Not Applicable
Size ..... 24" x 24" (.6096 m x .6096 m)
Flammability ..... ASTM E 648 Class 1 (Glue Down)
Smoke Density ..... ASTM E 662 Less Than 450
Static Propensity ..... AATCC-134 Under 3.5 KV
IAQ Green Label Plus 1098
CRI Appearance Retention Rating ..... Heavy Traffic
Warranties: Lifetime Limited Modular Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static