



Mesmerized Modular



65404 Crush



67410 Jealousy



84406 Wink



84407 Nice Tan



86414 Kiss



88408 Sultry



96413 Anticipation



99411 Indulgence

#### PRODUCT SPECIFICATIONS

|                            |                                     |                                       |                                                    |
|----------------------------|-------------------------------------|---------------------------------------|----------------------------------------------------|
| STYLE NAME .....           | Mesmerized Modular                  | DENSITY .....                         | 7,154                                              |
| STYLE NUMBER .....         | KT174                               | WEIGHT DENSITY .....                  | 257,544                                            |
| COLLECTION .....           | Another Infatuation                 | PRIMARY BACKING .....                 | Not Applicable                                     |
| PRODUCT TYPE .....         | Modular                             | BACKING MATERIAL .....                | EcoFlex ICT                                        |
| INSTALLATION METHOD .....  | Monolithic                          | SECONDARY BACKING .....               | None                                               |
| CONSTRUCTION .....         | Tufted                              | PATTERN REPEAT .....                  | Not Applicable                                     |
| SURFACE APPEARANCE .....   | Textured Patterned Cut and Loop     | SIZE .....                            | 24" x 24" (.6096 m x .6096 m)                      |
| NYLON TYPE .....           | Colorstrand Nylon and Ultron Nylon, | FLAMMABILITY .....                    | ASTM E 648 Class 1 (Glue Down)                     |
|                            | Type 6,6                            | SMOKE DENSITY .....                   | ASTM E 662 Less than 450                           |
| GAUGE .....                | 1/12 (47.00 rows per 10 cm)         | STATIC PROPENSITY .....               | AATCC-134 Under 3.5 KV                             |
| PILE WEIGHT .....          | 31.0 oz. per sq. yd (1051 g/m2)     | IAQ GREEN LABEL PLUS .....            | 1098                                               |
| PILE THICKNESS .....       | .156" (3.96 mm)                     | CRI APPEARANCE RETENTION RATING ..... | Severe Traffic                                     |
| STITCHES PER INCH .....    | 14.0 (55.12 per 10 cm)              | WARRANTIES:                           | Lifetime Limited Modular Warranty, Lifetime Static |
| DYE METHOD .....           | Solution Dyed/Space Dyed            |                                       |                                                    |
| PROTECTIVE TREATMENT ..... | Sentry Plus                         |                                       |                                                    |