



MODULAR SPECIFICATIONS

Style Number.....GT143
 Style NameWork It! Modular 26
 Constructiontufted
 Surface Texture.....Level Multi-Colored Loop
 Gauge1/10 (39.37 rows per 10 cm)
 Density.....6118
 Weight Density.....159068
 Sustainable Content ...Contains a minimum 35% pre-consumer recycled content by total weight
 Stitches Per Inch.....8.5 (33.46 per 10 cm)
 Finished Pile Thickness......153" (3.89 mm)
 Dye MethodSolution Dyed/Space Dyed
 Backing Material.....EcoFlex ICT
 Fiber TypeDuracolor® Premium Fiber
 Fiber TechnologyDuracolor® by LEES Stain Resistant System.
 Passes GSA requirements for permanent stain resistant carpet.
 Face Weight.....26 oz. per sq. yd. (882 g/m2)
 Installation Method.....Monolithic
 IAQ Green Label Plus..1098
 CRI Rating.....Severe Traffic
 Pattern Repeat.....Not Applicable
 WarrantiesLifetime Limited Modular Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static



214
SANDY SHORE



218
HAMMERED TIN



228
NATURAL HYBRID



311
CHAMELEON FOIL



312
ENRICHED GARNET



317
VELVET UNDER-
GROUND



322
SUNDRIED TOMATO



324
GROUNDED EARTH



327
TWILIGHT FORMAT



337
SLATENED SKY



418
BURNISHED IRON



421
METAL WORKS