X-Factor Modular

X-Factor Modular

7558 Secret Agent

7589 Cloak & Dagger

7638 Hush Hush

7877 Disguise

7889 Undercover

7936 Incognito

7979 Confidential

PRODUCT SPECIFICATIONS

Style Name ..... X-Factor Modular
Style Number BT212
Product Type ..... Modular
Installation Method ..... Brick Ashlar, Quarter Turn
Construction ..... Tufted
Surface Appearance ..... Level Patterned Loop
Nylon Type ..... Colorstrand® SD Nylon
Gauge ..... 1/10 (39.37 rows per 10 cm)
Pile Thickness ..... 107" (2.72 mm)
Stitches Per Inch ..... 8.0 (31.50 per 10 cm)
Dye Method ..... Solution Dyed
Protective Treatment ..... Sentry Plus
Density 4,710
Weight Density 65,940

Backing Material ..... EcoFlex ICT
Pattern Repeat ..... Not Applicable
Size ..... 24" x 24" (.6096 m x .6096 m)
Flammability ..... ASTM E 648 Class 1 (Glue Down)
Smoke Density ..... ASTM E 662 Less Than 450
Static Propensity ..... AATCC-134 Under 3.5 KV
IAQ Green Label Plus 1098
CRI Appearance Retention Rating ..... Severe Traffic
Warranties: Lifetime Limited Modular Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, Lifetime Static