


Emotion | 6254


Broadloom




Colorways




1930
Jump for Joy



3945
Singing the Blues



5933
Tickled Pink



7937
Up in Arms

Product Specifications

Construction	Textured Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	30 oz./sy (1017 grams/m ²)
Pile Density	8,209 oz./sy (304.58 kg/m ³)
Pattern Repeat	24" w x 36" l approx. (60.96 cm x 91.44 cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	12 stitches/in (4.72 stitches/cm)
Standard Size	12 ft (3.66 m)
Lifetime Warranties	Protection from Delamination Failure, Tuft Bind Strength (edge ravel, yarn pulls, zipping), Fiber Performance for Wear, Fiber Performance for Static, Colorfastness to Light and Atmospheric Contaminants, Stain Removal

Environmental Specifications & Tests

Sustainable Carpet Assessment Standard	NSF Gold
Indoor Air Quality	GLP 5055
Total Recycled Content	13%-24%
Pill Test	Yes
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
Lightfastness	Yes
ADA Compliance	Compliant for Accessible Routes

Special Treatments

ProTex® (Soil Release)	Yes
ProSept® (Antimicrobial)	Optional
Stain/Bleach Resistant	Yes

Coordinating Products

[Link](#)

