

Impact | 7978

Modular



Colorways



1450
Mingle



1451
Meld



1452
Blend




1453
Unite



1454
Combine



1455
Join



1456
Meet

Product Specifications

Construction	Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution/Yarn Dyed
Nylon Fiber Type	Encore® BCF (with recycled content)
Face Weight	20 oz./sy (678 grams/m ²)
Pile Density	6,410 oz./sy (222.48 kg/m ³)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	12.1 stitches/in (4.76 stitches/cm)
Standard Size	24" x 24" (60.96 cm x 60.96 cm)
Lifetime Warranties	Protection from Moisture Penetration, Protection from Delamination Failure, Dimensional Stability, Tuft Bind Strength (edge ravel, yarn pulls, zipping), Fiber Performance for Wear, Fiber Performance for Static

Environmental Specifications & Tests

Sustainable Carpet Assessment Standard	N/A
Indoor Air Quality	GLP 9716
Total Recycled Content	14%-19%
Pill Test	Yes
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
Lightfastness	Yes
ADA Compliance	Compliant For Accessible Routes

Special Treatments

ProTex® (Soil Release)	Yes
ProSept® (Antimicrobial)	Optional

Coordinating Products

Coordinates Collection	Coalesce, Collaborate, Mix, Merge, Fuse
-------------------------------	---

Installation Methods

Installation Methods	Quarter Turn, Monolithic, Ashlar, Brick
-----------------------------	---



Goods to Go
Quick Ship Goods