

Impulse II | 7236


Modular




### Colorways



1405  
Place a Bet




1430  
Plant a Tree




1431  
Roll the Dice



1432  
Give it a Whirl



1433  
Sing a Song



3408  
Call an Old Flame



6404  
Burst Out Laughing



7410  
Get a Tatoo



7412  
Speak Your Mind



8400  
Take a Trip



8401  
Bend a Rule



8403  
Take a Dare

### Product Specifications

<b>Construction</b>	Level Loop
<b>Backing</b>	Nexus® Modular
<b>Dye Method</b>	Solution/Yarn Dyed
<b>Nylon Fiber Type</b>	Encore® BCF (with recycled content)
<b>Face Weight</b>	22 oz./sy (745 grams/m <sup>2</sup> )
<b>Pile Density</b>	7,524 oz./sy (276.32 kg/m <sup>3</sup> )
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/10 (3.94 rows/cm)
<b>Stitches Per Inch</b>	7.3 stitches/in (2.87 stitches/cm)
<b>Standard Size</b>	24" x 24" (60.96 cm x 60.96 cm)
<b>Lifetime Warranties</b>	Protection from Moisture Penetration, Protection from Delamination Failure, Dimensional Stability, Tuft Bind Strength (edge ravel, yarn pulls, zipping), Fiber Performance for Wear, Fiber Performance for Static

### Environmental Specifications & Tests

<b>Sustainable Carpet Assessment Standard</b>	N/A
<b>Indoor Air Quality</b>	GLP 9716
<b>Total Recycled Content</b>	14%-19%
<b>Pill Test</b>	Yes
<b>Flooring Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>Lightfastness</b>	Yes
<b>ADA Compliance</b>	Compliant For Accessible Routes

### Special Treatments

<b>ProTex® (Soil Release)</b>	Yes
<b>ProSept® (Antimicrobial)</b>	Optional

### Coordinating Products

Impulse II is designed to coordinate with many J+J/Invision styles.

### Installation Methods

<b>Installation Methods</b>	Quarter Turn, Monolithic, Ashlar, Brick
-----------------------------	---

