

Problem Solved | 7442

Modular



Colorways



1201
Superglue



1203
Fix-A-Flat



1204
Rubber Band



1205
Band-Aid



1207
Gorilla Glue



1208
Staple Gun



1209
Reboot



1210
Duct Tape

Product Specifications

Construction	Textured Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (745 grams/m2)
Pile Density	5,657 oz./sy (209.89 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	9.3 stitches/in (3.66 stitches/cm)
Standard Size	24" x 24" (60.96 cm x 60.96 cm)
Lifetime Warranties	Protection from Moisture Penetration, Protection from Delamination Failure, Dimensional Stability, Tuft Bind Strength (edge ravel, yarn pulls, zippering), Fiber Performance for Wear, Fiber Performance for Static, Colorfastness to Light and Atmospheric Contaminants, Stain Removal

Environmental Specifications & Tests

Sustainable Carpet Assessment Standard	N/A
Indoor Air Quality	GLP 9716
Total Recycled Content	14%-19%
Pill Test	Yes
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
Lightfastness	Yes
ADA Compliance	Compliant For Accessible Routes

Special Treatments

ProTex® (Soil Release)	Yes
ProSept® (Antimicrobial)	Optional
Stain/Bleach Resistant	Yes

Coordinating Products

Corporate Values Too Collection	Quick Fix, Solutions
--	----------------------

Installation Methods

Installation Methods	Quarter Turn, Ashlar, Brick
-----------------------------	-----------------------------

