

Pulp | 7607

Modular



Colorways



Product Specifications

Construction	Tip Sheared Loop
Backing	eKo® Modular
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	24 oz./sy (813 grams/m ²)
Pile Density	8,435 oz./sy (312.96 kg/m ³)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	10.3 stitches/in (4.06 stitches/cm)
Standard Size	24" x 24" (60.96 cm x 60.96 cm)
Lifetime Warranties	Protection from Moisture Penetration, Protection from Delamination Failure, Dimensional Stability, Tuft Bind Strength (edge ravel, yarn pulls, zipping), Fiber Performance for Wear, Fiber Performance for Static, Colorfastness to Light and Atmospheric Contaminants, Stain Removal

Environmental Specifications & Tests

Sustainable Carpet Assessment Standard	NSF Platinum
Indoor Air Quality	GLP 3575
Total Recycled Content	35%-44%
Pill Test	Yes
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
Lightfastness	Yes
ADA Compliance	Compliant For Accessible Routes

Special Treatments

ProTex® (Soil Release)	Yes
ProSept® (Antimicrobial)	Optional
Stain/Bleach Resistant	Yes

Coordinating Products

Paper Craft Collection	Mache, Mache Trace, Mesh, Montage, Mosaic, Shred
-------------------------------	--

Installation Methods

Installation Methods	Quarter Turn, Monolithic, Ashlar, Brick,
-----------------------------	--

