

Shantung Couture | 9161

Broadloom



Colorways



Product Specifications

Construction	Multi-Level Tip Shear Loop
Backing	PremierBac® Plus
Dye Method	Beck Dyed
Nylon Fiber Type	Ultron® Nylon BCF
Face Weight	32 oz./sy (1085 grams/m ²)
Pile Density	5,19 0oz./sy (192.56 kg/m ³)
Pattern Repeat	24" w x 24" l approx. (60.96 cm x 60.96 cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	12.0 stitches/in (4.72 stitches/cm)
Standard Size	12 ft (3.66 m)
Lifetime Warranties	Protection from Delamination Failure, Tuft Bind Strength (edge ravel, yarn pulls, zipping), Fiber Performance for Wear, Fiber Performance for Static

Environmental Specifications & Tests

Sustainable Carpet Assessment Standard	NSF Gold
Indoor Air Quality	GLP 3678
Total Recycled Content	13%-24%
Pill Test	Yes
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
Lightfastness	Yes
ADA Compliance	Compliant For Accessible Routes

Special Treatments

ProTex® (Soil Release)	Yes
ProSept® (Antimicrobial)	Optional

Coordinating Products

Second Nature Collection	K-2, Shantung, Tussah
---------------------------------	-----------------------

