



Specifications	Stewart Island	Stewart Island
Style Number	4SL4206200	4SL4206200
Product Construction	Tufted Cut & Loop	Tufted Cut & Loop
Fiber	100% New Zealand wool	100% New Zealand wool
Dye Method	Yarn Dye	Yarn Dye
Soil/Stain Protection		
Antimicrobial		
Secondary Backing	Action-Bac	
Yarn Weight	42 oz/yd ²	1424 g/m ²
Machine Gauge	1/8 in	31.5 ends/10 cm
Pile Height		
-High	.313 in	8 mm
-Medium		
-Low		
Stitches:	12 /in	47.244 ends/10 cm
Pile Density		
Total Thickness	.375	9.525
Size	12 ft	3.657 m
Pattern Repeat	1/2" (w) Stripe	1.2700 cm (w) Stripe
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static		
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	Action-Bac,Prestige PlusRC™,Optimum BarrierRC™	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.