

**shaw contract group®**

dean's list II teklok®

®

**performance broadloom specifications**

style name	dean's list ii teklok®	
style number	60570	
construction	pattern loop	
fiber	eco solution q® nylon	
dye method	100% solution dyed	
	english	metric
	-----	
pattern repeat	0.3130"w x 6.9060"l	7.95 mm w x 175.41 mm l
tufted weight	28.0	949.36 g/m²
gauge	1/10	39.37 per 10cm
stitches per inch	8.5	33.46 per 10cm
finished pile thickness	0.120	3.05 mm
total thickness	0.284	7.21 mm
average density	8400	311.47 kg/m³
product size	12 foot	3.66 m
primary backing	synthetic	
secondary backing	teklok®	
protective treatments	ssp® shaw soil protection	

**testing**

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

**warranties**

lifetime commercial limited

**installation method**

direct glue

**coordinating products**

**environmental certification**

green label plus certification number glp 2271  
 nsf140 gold  
 cradle to cradle silver certified



Specifications are subject to nominal manufacturing variances.  
 Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429