

shaw contract group®

divide
collection: turn-key

broadloom specifications

style name	divide	
style number	5A065	
construction	multi-level pattern loop	
fiber	eco solution q@nylon	
dye method	100% solution dyed	
	english	metric

pattern repeat	1.0"w x 2.20"l	25.40 mm w x 55.88 mm l
tufted weight	26.0	881.55 g/m²
gauge	1/10	39.37 per 10cm
stitches per inch	11.0	43.31 per 10cm
finished pile thickness	0.137	3.48 mm
total thickness	0.277	7.04 mm
average density	6832	253.33 kg/m³
product size	12 foot	3.66 m
primary backing	synthetic	
secondary backing	classcbac®	
protective treatments	ssp® shaw soil protection	

testing

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

warranties

10 year commercial limited

installation method

direct glue

coordinating products

blog, blog classcbac®, culture, digital, edit, equal, evolution, fossil, global, innovation, mecca, metro, space, terra, text, text classcbac®, venture capital

environmental certification

green label plus certification number glp 8472



Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429