

shaw contract group®

edit
collection: TURN-KEY

broadloom specifications

style name	edit	
style number	5A067	
construction	multi-level pattern loop	
fiber	eco solution q@nylon	
dye method	100% solution dyed	
	english	metric

pattern repeat	0.40"w x 0.60"l	10.16 mm w x 15.24 mm l
tufted weight	26.0	881.55 g/m ²
gauge	1/10	39.37 per 10cm
stitches per inch	10.0	39.37 per 10cm
finished pile thickness	0.146	3.71 mm
total thickness	0.272	6.91 mm
average density	6411	237.72 kg/m ³
product size	12 foot	3.66 m
primary backing	synthetic	
secondary backing	classcbac®	
protective treatments	ssp®shaw soil protection	

testing

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

warranties

10 year commercial limited

installation method

direct glue

coordinating products

blog, blog classcbac®, culture, digital, divide, equal, evolution, fossil, global, innovation, mecca, metro, space, terra, text, text classcbac®, venture capital

environmental certification

green label plus certification number glp 8472



Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429