

shaw contract group®

glow
collection: feeling
plush

broadloom specifications

| | |
|--------------|------------------------------|
| style name | glow |
| style number | 5A020 |
| construction | multi-level pattern cut/loop |
| fiber | eco solution q@nylon |
| dye method | 100% solution dyed |

| | english | metric |
|-------------------------|--------------------------|---------------------------|
| ----- | | |
| pattern repeat | 12.0"w x 24.0"l | 30.48 cm w x 60.96 cm l |
| tufted weight | 34.0 | 1,152.80 g/m ² |
| gauge | 1/10 | 39.37 per 10cm |
| stitches per inch | 11.0 | 43.31 per 10cm |
| finished pile thickness | 0.184 | 4.67 mm |
| total thickness | 0.336 | 8.53 mm |
| average density | 6652 | 246.65 kg/m ³ |
| product size | 12 foot | 3.66 m |
| primary backing | synthetic | |
| secondary backing | ultraloc@pattern | |
| protective treatments | ssp@shaw soil protection | |
| gsa approved product | yes | |



testing

| | |
|--------------------------|------------------|
| radiant panel | class I |
| nbs smoke | less than 450 |
| electrostatic propensity | less than 3.5 kv |

warranties

lifetime commercial limited

installation method

direct glue

coordinating products

glitz tile, luminosity tile, lustre, radiance tile, shimmer

environmental certification

| | |
|---------------------------------------|----------|
| green label plus certification number | glp 2271 |
| nsf140 gold | |
| cradle to cradle silver certified | |



Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429