

shaw contract group®

potential III 26
unitary

performance broadloom specifications

| | | |
|-------------------------|---------------------------|--------------------------|
| style name | potential iii 26 unitary | |
| style number | 60587 | |
| construction | textured loop | |
| fiber | solution q nylon | |
| dye method | 100% solution dyed | |
| | english | metric |
| | ----- | |
| pattern repeat | none | |
| tufted weight | 26.0 | 881.55 g/m ² |
| gauge | 1/8 | 31.50 per 10cm |
| stitches per inch | 9.0 | 35.43 per 10cm |
| finished pile thickness | 0.128 | 3.25 mm |
| total thickness | 0.298 | 7.57 mm |
| average density | 7313 | 271.16 kg/m ³ |
| product size | 12 foot | 3.66 m |
| primary backing | synthetic | |
| secondary backing | unitary | |
| protective treatments | ssp® shaw soil protection | |

testing

| | |
|--------------------------|------------------|
| radiant panel | class I |
| nbs smoke | less than 450 |
| electrostatic propensity | less than 3.5 kv |

warranties

10 year commercial limited

installation method

direct glue

coordinating products

environmental certification

green label plus certification number glp 2271



Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429