



Refract Light Modular



Product Specifications

Collection Name	Vector	
Style Number	I0288	
Product Type	Modular	
Construction	Multi-Level Pattern Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	96% Solution Dyed, 4% Yam Dyed	
	English	Metric
Gauge	1/12	47.2 per 10 cm
Stitches Per Inch	10.5	41.34 per 10 cm
Tufted Pile Height	3/32" Low - 6/32" High	2.38mm - 4.76mm
Tufted Yarn Weight	22 Oz.	745.93 g/m ²
Finished Pile Thickness	.109	2.8 mm
Width	24" X 24"	60.96 cm x 60.96 cm
Density	7,266	13.53 kilotex
Weight Density	159,852	
Pattern Repeat	None	
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Non-Woven Synthetic	
Secondary Backing	EcoWorx® Tile	

Performance Specifications

Radiant Panel	Class I
NBS Smoke	<450 (ASTM E-662)
Electrostatic Propensity	Less Than 3.5Kv

Warranty Information


Lifetime Commercial Limited

Installation Methods



Environmental

Green Label Plus Certification Number Certified GLP9968
 NSF 140 Certification Platinum Certified
 Cradle To Cradle Silver Certified



patcraft.com 800.241.4014