



Carlo EcoWorx® Performance Broadloom



**Product Specifications**

|                                |                                |                         |
|--------------------------------|--------------------------------|-------------------------|
| <b>Collection Name</b>         | Dolce                          |                         |
| <b>Style Number</b>            | 10259                          |                         |
| <b>Product Type</b>            | Broadloom                      |                         |
| <b>Construction</b>            | Multi-Level Pattern Loop       |                         |
| <b>Fiber Type</b>              | Eco Solution Q® Nylon          |                         |
| <b>Dye Method</b>              | 100% Solution Dyed             |                         |
|                                | <b>English</b>                 | <b>Metric</b>           |
| <b>Gauge</b>                   | 1/10                           | 39.4 per 10 cm          |
| <b>Stitches Per Inch</b>       | 11.0                           | 43.31 per 10 cm         |
| <b>Tufted Pile Height</b>      | 3/32" Low - 8/32" High         | 2.38mm - 6.35mm         |
| <b>Tufted Yarn Weight</b>      | 28 Oz.                         | 949.36 g/m <sup>2</sup> |
| <b>Finished Pile Thickness</b> |                                |                         |
| <b>Width</b>                   | 12 Foot                        | 3.66 m                  |
| <b>Density</b>                 | 5727                           | 10.66 kilotex           |
| <b>Weight Density</b>          | 0                              |                         |
| <b>Pattern Repeat</b>          | 3 5/8"W X 2 5/8"L              | 9.21 cm w x 6.67 cm l   |
| <b>Protective Treatments</b>   | SSP® Shaw Soil Protection      |                         |
| <b>Primary Backing</b>         | Woven Synthetic                |                         |
| <b>Secondary Backing</b>       | EcoWorx® Performance Broadloom |                         |

**Performance Specifications**

|                                 |                 |
|---------------------------------|-----------------|
| <b>Radiant Panel</b>            | Class I         |
| <b>NBS Smoke</b>                | Less Than 450   |
| <b>Electrostatic Propensity</b> | Less Than 3.5Kv |

**Warranty Information**


Lifetime Commercial Limited

**Installation Methods**

Direct Glue

**Environmental**

|  |                    |
|--|--------------------|
| <b>Green Label Plus Certification Number</b> | Certified GLP9968  |
| <b>NSF 140 Certification</b>                 | Platinum Certified |
| <b>Cradle To Cradle Silver Certified</b>     |                    |



patcraft.com 800.241.4014