



Moderne Ultraloc® Pattern



Product Specifications

Collection Name	The Archive	
Style Number	I0155	
Product Type	Broadloom	
Construction	Pattern Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	5/64	50.4 per 10 cm
Stitches Per Inch	12.0	47.24 per 10 cm
Tufted Pile Height	3/32" Low - 7/32" High	2.38mm - 5.56mm
Tufted Yarn Weight	66.64 Ozs./Sq. Yd	2,259.48 g/m ²
Finished Pile Thickness	0.154	3.9 mm
Width	12 Foot	3.66 m
Density	7013	13.06 kilotex
Weight Density	210,390	
Pattern Repeat	18"W X 18"L	45.72 cm w x 45.72 cm l
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Woven Synthetic	
Secondary Backing	Ultraloc® Pattern	

Performance Specifications

Radiant Panel	Class I
NBS Smoke	Less Than 450
Electrostatic Propensity	Less Than 3.5 KV

Warranty Information

Lifetime Commercial Limited

Installation Methods

Direct Glue

Environmental

Green Label Plus Certification Number	Certified GLP2271
NSF 140 Certification	Gold Certified
Cradle To Cradle Silver Certified	



patcraft.com 800.241.4014