



Cashmere Modular



Product Specifications

Collection Name	Sheer Decadence	
Style Number	Z6452	
Product Type	Modular	
Construction	Multi-Level Pattern Cut/Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.2 per 10 cm
Stitches Per Inch	12.0	47.24 per 10 cm
Tufted Pile Height	4/32" Low - 8/32" High	3.18mm - 6.35mm
Tufted Yarn Weight	30 Oz.	1,017.17 g/m ²
Finished Pile Thickness	0.153	3.9 mm
Width	24" X 24"	60.96 cm x 60.96 cm
Density	7059	13.14 kilotex
Weight Density	211,770	
Pattern Repeat	None	
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Non-Woven Synthetic	
Secondary Backing	EcoWorx® Tile	


Performance Specifications

Radiant Panel	Class I
NBS Smoke	Less Than 450
Electrostatic Propensity	Less Than 3.5 KV

Warranty Information

Lifetime Commercial Limited

Installation Methods



Environmental

Green Label Plus Certification Number Certified GLP9968
 NSF 140 Certification Platinum Certified
 Cradle To Cradle Silver Certified



patcraft.com 800.241.4014