



Plug In Ultraloc® Pattern



Product Specifications

Collection Name	All In One	
Style Number	Z6388	
Product Type	Broadloom	
Construction	Pattern Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	67% Solution Dyed / 33% Yarn Dyed	
	English	Metric
Gauge	1/10	39.4 per 10 cm
Stitches Per Inch	9.5	37.40 per 10 cm
Tufted Pile Height	4/32" Low - 7/32" High	3.18mm - 5.56mm
Tufted Yarn Weight	69.15 Ozs. / Yd. ²	2,344.58 g/m ²
Finished Pile Thickness	0.100	2.5 mm
Width	12 Foot	3.66 m
Density	10080	18.77 kilotex
Weight Density	282,240	
Pattern Repeat	None	
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Woven Synthetic	
Secondary Backing	Ultraloc® Pattern	
GSA Approved Product	Yes	



Performance Specifications

Radiant Panel	Class I
NBS Smoke	Less Than 450
Electrostatic Propensity	Less Than 3.5 KV

Warranty Information


Lifetime Commercial Limited

Installation Methods

Direct Glue

Environmental

Green Label Plus Certification Number	Certified GLP8472
NSF 140 Certification	Gold Certified
Cradle To Cradle Silver Certified	



patcraft.com 800.241.4014