



## Best Foot Forward Ultraloc® Pattern



### Product Specifications

<b>Collection Name</b>	None	
<b>Style Number</b>	I0104	
<b>Product Type</b>	Broadloom	
<b>Construction</b>	Pattern Loop	
<b>Fiber Type</b>	Eco Solution Q® Nylon	
<b>Dye Method</b>	100% Solution Dyed	
	<b>English</b>	<b>Metric</b>
<b>Gauge</b>	5/64	50.4 per 10 cm
<b>Stitches Per Inch</b>	10.0	39.37 per 10 cm
<b>Tufted Pile Height</b>	4/32" Low - 6/32" High	3.18mm - 4.76mm
<b>Tufted Yarn Weight</b>	26 Oz.	881.55 g/m <sup>2</sup>
<b>Finished Pile Thickness</b>	0.119	3.0 mm
<b>Width</b>	12 Foot	3.66 m
<b>Density</b>	7866	14.65 kilotex
<b>Weight Density</b>	204,516	
<b>Pattern Repeat</b>	5/8"W X 1 1/4"L	15.88 mm w x 31.75 mm l
<b>Protective Treatments</b>	SSP® Shaw Soil Protection	
<b>Primary Backing</b>	Woven Synthetic	
<b>Secondary Backing</b>	Ultraloc® Pattern	

### Performance Specifications

<b>Radiant Panel</b>	Class I
<b>NBS Smoke</b>	Less Than 450
<b>Electrostatic Propensity</b>	Less Than 3.5 KV

### Warranty Information

Lifetime Commercial Limited

### Installation Methods

Direct Glue

### Environmental

<b>Green Label Plus Certification Number</b>	Certified GLP2271
<b>NSF 140 Certification</b>	Gold Certified
<b>Cradle To Cradle Silver Certified</b>	



patcraft.com 800.241.4014