



Energy Ultraloc® Pattern



**Product Specifications**

<b>Collection Name</b>	Metropolitan	
<b>Style Number</b>	Z6399	
<b>Product Type</b>	Broadloom	
<b>Construction</b>	Multi-Level Pattern Cut/Loop	
<b>Fiber Type</b>	Eco Solution Q® Nylon	
<b>Dye Method</b>	100% Solution Dyed	
	<b>English</b>	<b>Metric</b>
<b>Gauge</b>	3/32	42.0 per 10 cm
<b>Stitches Per Inch</b>	15.0	59.06 per 10 cm
<b>Tufted Pile Height</b>	3/32" Low - 10/32" High	2.38mm - 7.94mm
<b>Tufted Yarn Weight</b>	36 Oz.	1,220.61 g/m <sup>2</sup>
<b>Finished Pile Thickness</b>	0.200	5.1 mm
<b>Width</b>	12 Foot	3.66 m
<b>Density</b>	6480	12.07 kilotex
<b>Weight Density</b>	233,280	
<b>Pattern Repeat</b>	9"W X 9 3/4"L	22.86 cm w x 24.77 cm l
<b>Protective Treatments</b>	SSP® Shaw Soil Protection	
<b>Primary Backing</b>	Woven Synthetic	
<b>Secondary Backing</b>	Ultraloc® Pattern	
<b>GSA Approved Product</b>	Yes	



**Performance Specifications**

<b>Radiant Panel</b>	Class I
<b>NBS Smoke</b>	Less Than 450
<b>Electrostatic Propensity</b>	Less Than 3.5 KV

**Warranty Information**


Lifetime Commercial Limited

**Installation Methods**

Direct Glue

**Environmental**

<b>Green Label Plus Certification Number</b>	Certified GLP8472
<b>NSF 140 Certification</b>	Gold Certified
<b>Cradle To Cradle Silver Certified</b>	



patcraft.com 800.241.4014