



Radical Ultraloc® Pattern



Product Specifications

Collection Name	None	
Style Number	I0015	
Product Type	Broadloom	
Construction	Pattern Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	60% Solution Dyed / 40% Yam Dyed	
	English	Metric
Gauge	1/10	39.4 per 10 cm
Stitches Per Inch	11.0	43.31 per 10 cm
Tufted Pile Height	4/32" Low - 7/32" High	3.18mm - 5.56mm
Tufted Yarn Weight	28 Oz.	949.36 g/m ²
Finished Pile Thickness	0.156	4.0 mm
Width	12 Foot	3.66 m
Density	6462	12.03 kilotex
Weight Density	180,936	
Pattern Repeat	0.750"W X 0.750"L	19.05 mm w x 19.05 mm l
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Woven Synthetic	
Secondary Backing	Ultraloc® Pattern	

Performance Specifications

Radiant Panel	Class I
NBS Smoke	Less Than 450
Electrostatic Propensity	Less Than 3.5 KV

Warranty Information

Lifetime Commercial Limited

Installation Methods

Direct Glue

Environmental

Green Label Plus Certification Number Certified GLP2271
 NSF 140 Certification Gold Certified
 Cradle To Cradle Silver Certified



patcraft.com 800.241.4014