



ANTICO SPECIFICATION

B145

Construction	Interloop (Patterned Loop)	Yarn Content	Antron Lumena® solution dyed nylon type 6,6 (an Environmentally Preferable Product certified by Scientific Certification Systems)
Width	12' 6" (Wider widths available)	Average Yarn Pile Height	.119"
Tufted Yarn Weight	20 oz./sq. yd.	Average Yarn Density	6007
Approximate Finished Weight	50 oz./sq. yd.	Primary Back	Polypropylene
Gauge	5/64	Secondary Back	Permian Bac™, this high performance versatile acrylic backing system for all applications, is ideally suited for healthcare and restaurants.
Pattern Repeat	6.25" (W) x 12.50" (L)	Product Collection	AMORE DI ARTE COLLECTION
Custom Colors	Custom colors are available. For details, please contact your Atlas sales associate.		
Alternative Backing Systems	This product is available with ACTION-BAC, PERMIAM BAC™ MP* (moisture protection), an acrylic-based backing system (min. 360 lineal feet), FIRMA CUSHION BAC™ Polyurethane carpet backing manufactured with THE ENHANCER* Technology and BioCel** (min. 360 lineal feet), GEO BAC™ Polyurethane carpet backing manufactured with THE ENFORCER* Technology and BioCel** (min. 360 lineal feet), and TERRA CUSHION BAC™ Polyurethane carpet backing manufactured with BioCel** (min. 360 lineal feet). Standard overages apply. *Trademark of Atlas Carpet Mills. **Trademark of Universal Textile Technologies.		
Pattern Match & Installation Guidelines (Detailed installation instructions are available)	As with all patterned carpets, a perfect match at the seams may not be obtainable. However, for both stretch-in (recommend the use of 6" seaming tape) and glue down installations, a reasonable pattern match may be achieved by qualified and experienced professional installers utilizing power stretching and stay nailing techniques. Also, carpet should be brought into the space and unrolled 24 hours prior to installation for proper conditioning. These installation requirements must be considered in the original labor quotation. All seams and cut edges must be sealed with an Atlas approve "premium low-VOC" seam sealer containing a UV enhancer. Within corridors, avoid positioning carpet so that traffic flow falls across the width. When more than one dye lot is involved, the dye lots must be installed in dye lot sequence. A minor variation in color may be expected between dye lots.		
Additional Information	Chair pads are recommended, but not required for CARPET TILE, BROADLOOM with PERMIAM BAC™, PERMIAM BAC™ MP, FIRMA CUSHION BAC™ and GEO BAC™. Chair pads are required under castered chairs for BROADLOOM WITH LATEX and TERRA CUSHION BAC™. Watermarking or shading, a pile reversal phenomenon that can occasionally occur, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications when necessary in order to improve performance or to accommodate changes in material supply or manufacturing processes. WALK-OFF MATS are recommended at all entrances to minimize soiling.		
Quality Assurance	All carpets of Antron® nylon are subjected to a rigorous certification process (Antron® Performance Standards Program) to ensure they will perform.		
Soil Retardant	DuraTech® soil resistance treatment remains on carpets of Antron® nylon for over one million foot traffics		
Stain Resistance	Antron Lumena® solution dyed carries a limited lifetime warranty against staining.		
Colorfastness	Antron Lumena® solution dyed nylon carries a 10-year warranty against colorfastness to light.		
Easy Trim™	U.S. Patent No. 6,890,615 B2. Atlas' Easy Trim™ feature, marked by a black line, provides a small linear gap, allowing the installer to trim both edges back to the pattern, without damaging or cutting any of the yarns within the pattern.		
Static Control	Antron Lumena® solution dyed nylon carries a limited lifetime antistatic warranty not to exceed 3.5kV.		
Flammability Ratings	ASTM E648 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test: Less than 450.		
Indoor Air Quality	Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number GLP 2306.		
NSF-140 Certification	All Atlas carpets are NSF-140 certified.		
Environmental	Atlas follows an environmentally and socially responsible path in the development and manufacturing of all its products. Further, Atlas can provide certified reclamation of carpet being replaced. All of the above contribute toward LEED points. LOMAX™ Technology uses renewable energy (landfill gas) in the production of Styron latex carpet backings to reduce greenhouse gas emissions.		
Warranty	Antron Lumena® solution dyed nylon carries a Limited 10-year warranty.		
Additional Specification Information	Pattern lines, inherent in the pattern and construction of this product, which may be visible lengthwise, are not considered a manufacturing defect. Watermarking or shading, a pile reversal phenomenon that can occasionally occur in any carpet construction, regardless of fiber type, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications when necessary in order to improve performance and to accommodate changes in material supply or manufacturing processes.		
Trademarks	Antron® and the Antron® family of marks and logos are trademarks of INVISTA.		
© Copyright	This pattern is protected under federal copyright law and may not be duplicated without Atlas' express written permission.		

Atlas Carpet Mills, Inc.

Plant, Offices and Showroom:

2200 Saybrook Avenue
Los Angeles, CA 90040
(323) 724-9000 (800) 372-6274
FAX (800) 272-8527 FAX (323) 724-4526

Chicago Showroom:

The Merchandise Mart
222 Merchandise Mart Plaza, Suite 11-122
Chicago, IL 60654
(866) 527-9870 FAX (312) 527-9980

New York City Showroom:

New York Design Center
200 Lexington Ave., Suite 1314
New York, NY 10016
(800) 223-0323 FAX (212) 779-7905

Direct Access and Voice Mail: (800) 367-8188 (Ext: 2300 for SAMPLE and ORDER DESK) www.atlascarpetmills.com