

Construction	Interloop	Yarn Content	Antron Legacy® nylon type 6,6 (an Environmentally Preferable Product certified by Scientific Certification Systems)
Width	12' 6" (Wider widths available)	Average Yarn Pile Height	.163"
Tufted Yarn Weight	32 oz./sq. yd.	Average Yarn Density	6640
Approximate Finished Weight	62 oz./sq. yd.	Primary Back	Polypropylene
Gauge	5/64	Secondary Back	Action Bac™
Pattern Repeat	37.50" (W) x 37.50" (L)	Product Collection	MOD SQUAD COLLECTION
Custom Colors	The minimum order is 45 feet. Please allow a 5 foot overage from 45 to 100 feet, a 5% overage from 100 to 800 feet and a 3% overage above 800 feet.		
Alternative Backing Systems	This product is available with PERMIAN BAC™*, an acrylic based backing system (min. 100 lineal feet for 12' width), PERMIAN BAC™ MP* (moisture protection), an acrylic-based backing system (min. 360 lineal feet), FIRMA CUSHION BAC™ Polyurethane carpet backing manufactured with THE ENHANCER* Technology and BioCel** (min. 360 lineal feet), GEO BAC™ Polyurethane carpet backing manufactured with THE ENFORCER* Technology and BioCel** (min. 360 lineal feet), and TERRA CUSHION BAC™ Polyurethane carpet backing manufactured with BioCel** (min. 360 lineal feet). Standard overages apply. *Trademark of Atlas Carpet Mills. **Trademark of Universal Textile Technologies.		
Pattern Match & Installation Guidelines (Detailed installation instructions are available)	As with all patterned carpets, a perfect match at the seams may not be obtainable. However, for both stretch-in (recommend the use of 6" seaming tape) and glue down installations, a reasonable pattern match may be achieved by qualified and experienced professional installers utilizing power stretching and stay nailing techniques. Also, carpet should be brought into the space and unrolled, 24 hours prior to installation for proper conditioning. To obtain a reasonable texture match, this carpet must be trimmed back a minimum of 1 inch from each edge. All seams must be sealed with an Atlas approved "premium low-voc" seam sealer. Within corridors, avoid positioning carpet so that traffic flow falls across the width. When more than one dye lot is involved, the dye lots must be installed in dye lot sequence. A minor variation in color may be expected between dye lots.		
General Guidelines	Chair pads are required to protect seams and deter accelerated wear in areas where casters chairs are used. Walk-off mats are recommended at all entrances to minimize soiling. This carpet is intended only for use as a floor covering. Atlas will not assume any liability when this carpet is used in any other manner.		
Quality Assurance	All certified carpets of Antron® Legacy nylon meet strict performance and construction standards of the Invista™ performance standards program assuring the highest quality carpet. The Type 6,6 nylon polymer of Antron Legacy® provides superior resistance to crushing, matting, stain penetration and wear.		
Soil Retardant	Duratech® soil resistance treatment provides superior soil resistance.		
Static Control	Antron® Legacy nylon carries a limited lifetime antistatic warranty not to exceed 3.5kV.		
Easy Trim™	U.S. Patent No. 6,890,615 B2. Atlas' Easy Trim™ feature, marked by a black line, provides a small linear gap, allowing the installer to trim both edges back to the pattern, without damaging or cutting any of the yarns within the pattern.		
Flammability Ratings	ASTM E648 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test; less than 450.		
Indoor Air Quality	Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number GLP 4428.		
NSF-140 Certification	All Atlas broadloom is certified Gold under NSF-140.		
Environmental Position	Atlas follows an environmentally and socially responsible path in the development and manufacturing of all its products. Further, Atlas can provide certified reclamation of carpet being replaced. All of the above contribute toward LEED points. LOMAX™ Technology uses renewable energy (landfill gas) in the production of Styron latex carpet backings to reduce greenhouse gas emissions.		
Warranty	Antron® Legacy nylon carries a limited 10-year warranty.		
Additional Specification Information	Pattern lines, inherent in the pattern and construction of this product, which may be visible lengthwise or widthwise, are not considered a manufacturing defect. Watermarking or shading, a pile reversal phenomenon that can occasionally occur in any carpet construction, regardless of fiber type, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications when necessary in order to improve performance and to accommodate changes in material supply or manufacturing processes.		
Trademarks	Antron Legacy® is a registered trademark for carpet fiber. DuraTech® is a registered trademark for soil resistant treatment. LOMAX™ Technology is a Styron registered trademark. Action Bac™ is a trademark of Propex.		
© Copyright	This pattern is protected under federal copyright law and may not be duplicated without Atlas' express written permission.		

Atlas Carpet Mills, Inc.

Plant, Offices and Showroom:

2200 Saybrook Avenue
 Los Angeles, CA 90040
 (323) 724-9000 (800) 372-6274
 FAX (800) 272-8527 FAX (323) 724-4526

Chicago Showroom:

The Merchandise Mart
 222 Merchandise Mart Plaza, Suite 11-122
 Chicago, IL 60654
 (866) 527-9870 FAX (312) 527-9980

New York City Showroom:

New York Design Center
 200 Lexington Ave., Suite 1314
 New York, NY 10016
 (800) 223-0323 FAX (212) 779-7905

Direct Access and Voice Mail: (800) 367-8188 (Ext: 2300 for SAMPLE and ORDER DESK) www.atlascarpetmills.com