

|   |  |                                 |   |
|---|--|---------------------------------|---|
| <b>Construction</b>   | Ultraweave   | <b>Yarn Content</b>             | Antron Legacy® nylon type 6,6 (an Environmentally Preferable Product certified by Scientific Certification Systems) |
| <b>Width</b>  | 12' 6" (13'6" width available)   | <b>Average Yarn Pile Height</b> | .173"   |
| <b>Tufted Yarn Weight</b>   | 31 oz./sq. yd.   | <b>Average Yarn Density</b>     | 6,243   |
| <b>Approximate Finished Weight</b>  | 65 oz./sq. yd.   | <b>Primary Back</b>             | Polypropylene   |
| <b>Gauge</b>  | 5/64   | <b>Secondary Back</b>           | Action Bac™   |
| <b>Pattern Repeat</b>   | 37.50" (W) x 37.50" (L)  | <b>Product Collection</b>       | ARCHEOLOGIQUE COLLECTION  |
| <b>Stocking &amp; Custom Colors</b>   | 24 stocking colors. Custom colors available at minimum yardage. (Please contact your local Atlas sales representative)   |                                 |   |
| <b>Custom Colors</b>  | Available at minimum yardage. (Please contact your sales representative)   |                                 |   |
| <b>Alternative Backing Systems</b>  | This product is available with PERMIAN BAC™, an acrylic-based backing system (no minimum for standard width), PERMIAN BAC™,MP providing moisture protection (min. 360 lineal feet), FIRMA CUSHION BAC™ Polyurethane carpet backing (min. 100 lineal feet),ELEMENT CUSHION BAC™ Polyurethane carpet backing (min. 100 lineal feet), TERRA CUSHION BAC™ Polyurethane carpet backing (min. 100 lineal feet), GEO BAC™ Polyurethane carpet backig (min.100 lineal feet), and CAMBRIAN BAC™ Polyurethane carpet backing (min. 100 lineal feet). Standard overages apply. ™ Trademark of Atlas Carpet Mills.   |                                 |   |
| <b>Pattern Match &amp; Installation Guidelines (Detailed installation instructions are available)</b> | As with all patterned carpets, a perfect match at the seams may not be obtainable. However, a reasonable pattern match may be achieved by qualified and experienced professional installers utilizing power stretching and stay nailing techniques. Also, carpet should be brought into the space and unrolled, 24 hours prior to installation for proper conditioning. All seams and cut edges must be sealed with an Atlas approved "premium low-voc" seam sealer containing UV enhancer.  |                                 |   |
| <b>General Guidelines</b>   | All certified carpets of Antron® Legacy nylon meet strict performance and construction standards of the Invista performance standards program assuring the highest quality carpet. The type 6,6 nylon polymer of Antron Legacy® provides superior resistance to crushing, matting, stain penetration and wear  |                                 |   |
| <b>Quality Assurance</b>  | All certified carpets of Antron® Legacy nylon meet strict performance and construction standards of the Invista performance standards program assuring the highest quality carpet. The type 6,6 nylon polymer of Antron Legacy® provides superior resistance to crushing, matting, stain penetration and wear  |                                 |   |
| <b>Soil Retardant</b>   | DuraTech® soil resistance treatment remains on carpets of Antron® nylon for over one million foot traffics.  |                                 |   |
| <b>Static Control</b>   | Antron® Legacy nylon carries a limited lifetime antistatic protection warranty not to exceed 3.5kV.  |                                 |   |
| <b>Easy Trim™</b>   | U.S. Patent No 6,890,615 B2. Atlas' Easy Trim™ feature, marked by a black line, provides a small linear gap, allowing the installer to trim both edges back to the patterns, without damaging or cutting any of the yarns within the pattern.  |                                 |   |
| <b>Flammability Ratings</b>   | ASTM E668 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test: < 450.   |                                 |   |
| <b>Indoor Air Quality</b>   | Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number GLP 2306.   |                                 |   |
| <b>NSF-140 Certification</b>  | All Atlas BROADLOOM is NSF-140 certified, Gold.  |                                 |   |
| <b>Environmental Position</b>   | Atlas BROADLOOM, by total weight, contains 10% <u>post consumer recycled</u> content, Atlas CARPET TILES, by total weight, contains 21% recycled content; 10% <u>post industrial recycled</u> content and 11% <u>post consumer recycled</u> content. Atlas uses Invista's Antron® Legacy nylon type 6.6 which is an Environmentally Preferable Product. Further, Atlas participates in a reclamation program that collects and reclaims used carpet and carpet tiles, eliminating landfill disposal. All of the above contribute toward LEED points.<br><br>Broadloom styles are manufactured with LOMAX™ Technology utilizing renewable energy (landfill gas) in the production of Styron latex carpet backings to reduce <u>greenhouse gas</u> emissions |                                 |   |
| <b>Warranty</b>   | Antron® Legacy nylon carries a limited 10-year warranty. See written warranties.   |                                 |   |
| <b>Additional Specification Information</b>   | Chair pads are highly recommended under roller casters to preserve appearance and prevent accelerated wear.  |                                 |   |
| <b>Trademarks</b>   | Antron® and the Antron® family of marks and logos are trademarks of INVISTA.   |                                 |   |
| <b>© Copyright</b>  | This patterns are protected under federal copyright law and may not be duplicated without Atlas' express written permission.   |                                 |   |

## Atlas Carpet Mills, Inc.

### Plant, Offices and Showroom:

2200 Saybrook Avenue  
Los Angeles, CA 90040  
(323) 724-9000 (800) 372-6274  
FAX (800) 272-8527 FAX (323) 724-4526

### Chicago Showroom:

The Merchandise Mart  
222 Merchandise Mart Plaza, Suite 11-122  
Chicago, IL 60654  
(866) 527-9870 FAX (312) 527-9980

### New York City Showroom:

New York Design Center  
200 Lexington Ave., Suite 1314  
New York, NY 10016  
(800) 223-0323 FAX (212) 779-7905

**Direct Access and Voice Mail: (800) 367-8188 (Ext: 2300 for SAMPLE and ORDER DESK) [www.atlascarpetmills.com](http://www.atlascarpetmills.com)**