

Koroseal Wallcoverings®
A Division of RJF International Corporation
3875 Embassy Parkway
Fairlawn, OH 44333

KOROSEAL WALLCOVERINGS®
FACT SHEET
Pattern Name: SALERNO®

QUIK SPEC	U.S. UNITS	METRIC UNITS
Total Weight	15.0 oz./ linear yard	465 g./ linear meter
	10.0 oz./square yard	339 g./square meter
Roll Width	53/54 in.	135/137 cm.
Thickness	0.0067 in.	0.17 mm.
Fabric: Sheeting	Federal Spec: CCC-W-408A, Type I	CFFA Spec: CFFA-W-101C Type I, Class A
Fire Testing	NFPA 101® Life Safety Code®	
	NFPA 255 (ASTM E84, CAN S102M) Tunnel Test ¹ : Class A Rating	U.L. Labeled and Listed
	NFPA 286 Corner Burn Test ² : Meets requirements for Flame spread smoke developed and flashover	
Repeat	Vertical: N/A	Horizontal: N/A
1. When tested on GRC board with A-848-B adhesive	2. When tested on 5/8" type-x gypsum board with A-848-B adhesive	

COLORLINE	PATTERN NUMBER/NAME OF COLORS
DESCRIPTION OF THE PATTERN:	A lightweight version of our classic Chimayo pattern.
	Available in 6 colorways.
HANGING INSTRUCTIONS:	Match: Random Match Reverse Strips: Yes
SPECIAL INSTRUCTIONS (if any):	
C515-14	
C515-16	
C515-19	
C515-26	
C515-97	
C515-99	